CERTIFICATE

Certificate number	16082 Rev.2	Replaces	16082 Rev.1
Issued	18/12/2023	First edition	20/12/2018
Report number	PKC0002533	Expiry date	17/12/2028
Page	1 of 1	Contract number	PKC0002392

Product Certificate Solar Thermal Products

License holder: **Pleion S.p.A.**
Via Venezia 11 – 37053 Cerea (VR), Italy

Production site(s): Pleion S.p.A.
Via Venezia 11 – 37053 Cerea (VR), Italy

Product Solar thermal collector

Model(s): X-RAY 21 R

Kiwa Cermet Italia hereby declares that the product can be considered complying to the testing requirements and is entitled to use the Solar Keymark Label, based upon the following aspects:

Laboratory testing of the solar thermal products, which are performed by an accredited laboratory in accordance to EN ISO/IEC 17025:2005 -see annex-, using the following standards:

- ISO 9806:2013
  Solar Energy – Solar Thermal Collectors – Test Methods

Specific CEN Keymark Scheme Rules for Solar Thermal Products SKN_N0444R6.

Periodic Inspection of the Factory site(s) performed by Kiwa Cermet Italia.
A description of the test results is given in the annex to this certificate.

This certificate is issued in accordance with the Kiwa Cermet Italia regulations.
Publication of the certificate is allowed.
The validity of this certificate is subject to the positive result of periodic surveillance visits.
The validity of this certificate can be verified on request at the following e-mail address: energy@kiwacermet.it.
Any total or partial reproduction of this document in any form, without Kiwa Cermet Italia express authorization, is prohibited.

Industry Division Manager
Maurizio Lorenzon

Kiwa Cermet Italia S.p.A.
Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl
Via Cadriano, 23
40057 Granarolo dell'Emilia (BO)
Tel +39.051.459.3.111
Fax +39.051.763.382
E-mail: info@kiwacermet.it
www.kiwa.it

ACCREDIA
L'ENTE ITALIANO DI ACCREDITAMENTO

PRD N° 069B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC
Signatory of EA, IAF and ILAC Mutual Recognition Agreements

034

Annex to Solar Keymark Certificate

Licence Number	**16082 Rev.2**
Date issued	**2023-12-18**
Issued by	**Kiwa Cermet Italia S.p.A.**

Licence holder	**Pleion S.p.A.**	**Country**	Italy
Brand (optional)		**Web**	https://www.pleion.it
Street, Number	Via Venezia, 11	**E-mail**	info@pleion.it
Postcode, City	37053, Cerea (VR)	**Tel**	+39 0442320295

Collector Type	Evacuated tubular collector

Collector name	**Gross area (A_G)**	**Gross length**	**Gross width**	**Gross height**	**Power output per collector** Gb = 850 W/m2, Gd = 150 W/m2 & u = 1.3 m/s $\vartheta_m - \vartheta_a$					
					0 K	10 K	30 K	50 K	70 K	94 K
	m²	mm	mm	mm	W	W	W	W	W	W
X-RAY 21 R	4.45	2,316	1,921	114	2,710	2,677	2,598	2,501	2,386	2,223
					0	0	0	0	0	0
Power output per m² gross area					609	602	584	562	536	499

Performance parameters test method	Steady state - outdoor									
Performance parameters (related to A_G)	η0, b	a1	a2	a3	a4	a5	a6	a7	a8	Kd
Units	-	W/(m²K)	W/(m²K²)	J/(m³K)	-	J/(m²K)	s/m	W/(m²K⁴)	W/(m²K⁴)	-
Test results	0.611	0.690	0.005	0.000	0.00	50,900	0.000	0.00	0.0E+00	0.98

Incidence angle modifier test method		Steady state - outdoor							
Incidence angle modifier	Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
Transversal	$K_{\theta T,coll}$	1.01	1.02	1.06	1.10	1.14	1.16	1.12	0.56	0.00
Longitudinal	$K_{\theta L,coll}$	1.00	0.99	0.98	0.95	0.91	0.84	0.69	0.35	0.00

Heat transfer medium for testing	Water		
Flow rate for testing (per gross area, A_G)	dm/dt	0.020	kg/(sm²)
Maximum temperature difference during thermal performance test	$(\vartheta_m-\vartheta_a)_{max}$	64.3	K
Standard stagnation temperature (G = 1000 W/m²; ϑ_a = 30 °C)	ϑ_{stg}	279	°C
Maximum operating temperature	ϑ_{max_op}	130	°C
Maximum operating pressure	$p_{max,op}$	1000	kPa

Testing laboratory	ENEA Centro Ricerche Trisaia	http://www.trisaia.enea.it	
Test report(s)	RP.2018.COL.202.1	**Dated**	18/12/2018

Comments of testing laboratory Ver. 6.2 (13.01.2022)

ENEA
TERIN-STSN
Dr. Vincenzo Sabatelli

Annex to Solar Keymark Certificate	Licence Number	16082 Rev.2
Supplementary Information	Issued	2023-12-11

Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m

Standard Locations	Athens			Davos			Stockholm			Würzburg		
Collector name ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
X-RAY 21 R	4,808	4,423	3,966	4,206	3,791	3,337	3,031	2,686	2,326	3,249	2,885	2,500
Gross Thermal Yield per m² gross area	1,080	994	891	945	852	750	681	604	523	730	648	562
Annual efficiency, η_a	61%	56%	50%	58%	52%	46%	58%	52%	45%	59%	52%	45%
Fixed or tracking collector	Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane	1765 kWh/m²			1630 kWh/m²			1166 kWh/m²			1244 kWh/m²		
Mean annual ambient air temperature	18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode	South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature ϑm (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.2 (13.01.2022). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/

Additional Information

Collector heat transfer medium				Water-Glycole	
The collector is deemed to be suitable for roof integration				No	
The collector was tested successfully under the following conditions:					
Climate class (A+, A, B or C)				B	--
G (W/m²) >	900	ϑ_a (°C) >	15	H_x (MJ/m²) >	540
Maximum tested positive load				2416	Pa
Maximum tested negative load				2014	Pa
					m

Additional collector attribute(s)

Using external power source(s) for normal operation	No	Active or passive measure(s) for self-protection	No
Co-generating thermal and electrical power	No	Façade collector(s)	No

Energy Labelling Information

	Reference Area, A_{sol} (m²)
X-RAY 21 R	4.45

Additional Informative Technical Data

Hydraulic Designation Code	Aperture Area, A_a (m²)
21-V-1122S-A:X-C:X	4.02

Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}

Collector efficiency (η_{col})	57%

Remark: Collector efficiency (ηcol) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m², expressed in % and rounded to the nearest integer. Deviating from the regulation ηcol is based on reference area (Asol) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.

Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}

Zero-loss efficiency (η_0)	0.61	--
First-order coefficient (a_1)	0.69	W/(m²K)
Second-order coefficient (a_2)	0.005	W/(m²K²)
Incidence angle modifier IAM (50°)	1.03	--

Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.

Kiwa Cermet Italia S.p.A. ● Via Cadriano, 23 ● 40057 Granarolo dell'Emilia (BO) ● Italy
Tel: +39 0514593111 ● Fax: +39 051763382 ● E-Mail: info@kiwacermet.it ● www.kiwa.it